



Empowering Wireless Connectivity



Embed +60 Years of Wireless Expertise & Performance Into Your Connected Solution

THE CEL ADVANTAGE



Performance

- Best in class wireless connectivity
- Lowest system power consumption
- Product testing & verification



AcCELERate TTM

- 2-day in-person training
- Quick start guides/resources
- Fast prototyping



Commercial Grade Quality & Reliability

- 100% RF tested w/traceability
- Extensive JESD22 qualifications
- No field failures, RMAs, truck rolls...



Technical Support & Expertise

- HW, FW, Antenna design guides
- Comprehensive design reviews
- Certification/compliance



Home Automation



Building Automation



Connected Lighting



Industrial



Smart Energy



NEW

Multi-Protocol IoT Connectivity Solution

- Based on Qualcomm's QCA4020 chip set
- Wi-Fi, BLE, ZigBee, Thread
 - Dual-band 1x1 802.11 a/b/g/n
 - BLE5.0
 - ZB 3.0
 - Thread v1.1
- Implementation options:
 - Hostless...Integrated Cortex-M4F, SRAM, Flash & peripherals for application, ThreadX and FreeRTOS
 - Hosted...SDIO/SPI/UART interfaces for external host MCU, driver source code and APIs
- Dedicated CPUs for Wi-Fi and 802.15.4 stacks
- Concurrent Wi-Fi and 802.15.4 operation
- Coexistence manager
- Low power Wi-Fi and 802.15.4 operation modes
- Pre-integrated s/w for HomeKit and OCF, AWS IoT SDK, and Microsoft Azure IoT Device SDK



COMING SOON



High-performance & Ultra Low-power Wi-Fi & BT for Hosted Applications

- Based on Qualcomm's QCA9377-x
- Dual-band 1x1 802.11 b/g/n/a/ac Wave2 & BT5.0
- SDIO and USB interface options
- +20dBm
- On-board and external antenna options
- Miniature form factor
- Industrial Temp.
- Drivers: Linux, Windows 10, and Android

PRODUCT OFFERINGS & TECHNICAL INFORMATION



Based on EM3588 SoC



Based on EM357 SoC



Based on EFR32MG12 SoC



MeshConnect Products

	EM358x Mini Modules		EM357 Mini Modules		ZB3212F6R Multi-Mode	EM35x USB Sticks	
	Standard	Extended Range	Standard	Extended Range	Standard	Standard	Extended Range
MCU							
Radio Parameters	2405 to 2480 MHz / DSSS / IEEE 802.15.4		2405 to 2480 MHz / DSSS / IEEE 802.15.4		2405 to 2480 MHz / DSSS / IEEE 802.15.4	2405 to 2480 MHz / DSSS / IEEE 802.15.4	
Transceiver Chipset	Silicon Labs™ EM3588 32 bit, ARM® Cortex™ - M3		Silicon Labs™ EM357 32 bit, ARM® Cortex™ - M3		Silicon Labs™ EFR32MG12 32 bit, ARM® Cortex™ - M4	Silicon Labs™ EM35x 32 bit, ARM® Cortex™ - M3	
Memory on Chip	512 kB Flash, 64 kB RAM		192 kB Flash, 12 kB RAM		1MB Flash, 256kB RAM	192 kB Flash, 12 kB RAM	
Supplemental Memory	-		-		-	1 MB Flash	
Inputs/Outputs	Up to 23		Up to 22		Up to 24	N/A	
USB	USB 2.0 (full speed)		-		-	USB 2.0 (full speed)	
NETWORK							
Protocol	Zigbee, Thread		Zigbee		Zigbee, Thread, BTLE	USB, Zigbee, Thread	
Mesh Networks	✓		✓		✓	✓	
Over-the-Air Data Rate	250 kbps		250 kbps		250kbps	250 kbps	
Over-the-Air Security	128-bit AES Encryption		128-bit AES Encryption		128/256-bit AES Encryption	128-bit AES Encryption	
Software/ZigBee Stack	EmberZNet PRO™ (ZigBee PRO)		EmberZNet PRO™ (ZigBee PRO)		EmberZNet PRO™	EmberZNet PRO™ (ZigBee PRO)	
PERFORMANCE							
Tx Output Power	+ 8 dBm	+ 20 dBm	+ 8 dBm	+ 20 dBm	+20dBm	+ 8 dBm	+ 20 dBm
Rx Sensitivity	- 100 dBm	- 103 dBm	- 100 dBm	- 103 dBm	-101dBm	- 100 dBm	- 103 dBm
RF Link Budget	+108 dB	+123 dB	+108 dB	+123 dB	+121dBm	+108 dB	+123 dB
Power Supply Voltage	2.1 to 3.6 V		2.1 to 3.6 V		2.4-3.8V	4.0 to 5.25 V	
Rx Current	30mA	34mA	30mA	34mA	12mA	51mA	55mA
Tx Current@Max Power	44mA	150mA	44mA	150mA	120mA	65mA	165mA
Sleep/Suspend Current	2.4µA		1.0µA		.43uA	0.24µA	
Dimensions	23.9 x 16.6 x 3.9mm (0.94 x 0.655 x 0.152in)		23.9 x 16.6 x 3.9mm (0.94 x 0.655 x 0.152in)		23.9x16.6.x3.9mm	52.7 x 24.9 x 9.98mm (2.075 x 0.984 x 0.393in)	
Footprint Compatible	✓		✓		✓	-	
Integrated Antenna	✓		✓		✓	✓	
RF Port for External Antenna	✓		✓		✓	-	
Temperature Range	-40°C to 85°C		-40°C to 85°C		-40°C to +85°C	-30°C to 70°C	
CERTIFICATIONS							
FCC	✓	✓	✓	✓	✓	✓	✓
IC	✓	✓	✓	✓	✓	✓	✓
CE	✓	-	✓	-	-	✓	-
RoHS	✓	✓	✓	✓	✓	✓	✓
Part Numbers	ZICM3588SP0-1 ZICM3588SP0-1C*	ZICM3588SP2-2 ZICM3588SP2-2C*	ZICM357SP0-1 ZICM357SP0-1C*	ZICM357SP2-2 ZICM357SP2-2C*	ZB3212F6R4SP2-1,-1C	ZM357S-USB	ZM357S-USB-LR

* Part numbers ending in **SP0-1C** have an RF port for external antennas and are not FCC, IC or CE certified.
Part numbers ending in **SP2-2C** have an RF port for external antennas and are FCC and IC certified for a Nearson S181AH-2450S antenna.